

APOU7.S3598 - Proprietary Alarm Units Certified for Canada

Proprietary Alarm Units Certified for Canada

[See General Information for Proprietary Alarm Units Certified for Canada](#)

DIGITAL MONITORING PRODUCTS INC

S3598

2500 N Partnership Blvd

Springfield, MO 65803-8877 USA

Models XR100, XR100N, XR500, XR500N, XR500E burglar alarm control communicator, and Models XR550, XR350, XR150 (may be followed by any of the following -D (dialer), -E (encryption), and/or -N (network)) burglar alarm control communicator, provides line security Level IV and V on Internet, Intranet, LAN and WAN networks. Use with 16.5 V ac, 50 VA or 16 V ac, 56 VA or 16 V ac, 75 VA (from a Class 2, limited energy plug-in transformer). To be used with manufacturer's Model SCS-1R receiver.

Model SCS-1R receiver, Input: 120 V, 60 Hz, 900 mA, consisting of the subassemblies, Model SCS-150 processor card, Models SCS-100, SCS-104 line cards, Model SCS-101 Network interface, Model SCS-110 modem power supply, Model SCS-120 multibus power supply card, Model SCS-130 transformer card.

Accessories, Keypad, Models 7060, 7060A, 7160, 7160A, 7560, 7560A, 7061,7063, 7063A, 7163, 7163A, 7563, 7563A, 7070, 7070A, 7170, 7170A, 7570, 7570A, 7073, 7073A, 7173, 7173A, 7573, 7573A, 690, 693, 790, 793, 7760.

Accessory, digital cellular communicator, Models 463C, 463G. For use with burglar alarm control communicator models XR100, XR100N, XR500, XR500N, XR500E.

Accessory, digital cellular communicator, Models 263C, 263H. For use with burglar alarm control communicator models XR550, XR350, XR150 (may be followed by any of the following -D (dialer), -E (encryption), and/or -N (network)).

Accessories, Models 318, 318T, 318R, 318EXT battery harness.

Subassembly, transient suppression, Model 270 for RJ45 connection.

Subassembly: Digital Cellular Communicator, Models 263LTE, 263LTE-FN.

Subassembly, trouble sounder, Model 277CAN. For use with XR550, XR350, XR150.

Accessory, digital cellular communicator, Model 464-263C - Suitable for Line Security over CDMA network when used with model 263C.

Accessory, digital cellular communicator, Model 464-263H - Suitable for Line Security over HSPA+ network when used with model 263H.

Subassemblies: Wiegand interface module, Model 734; Model 734 with Enclosure can also be used as an Accessory.

Accessory, Zone Expanders, Model 711, 711S, 714, 715.

Accessory, Zone Expanders, Model 714-8, 714-16, 715-8, 715-16.

Last Updated on 2021-01-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

