

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No.:	7165-1157:0135	
CATEGORY:	7165 - FIRE ALARM CONTROL UNIT (COMMERCIAL)	
LISTEE:	Digital Monitoring Products, Inc. 2500 N. Partnership Blvd, Springfield, MO, 65803 Contact: Wilson, James 417-447-9697 Email: jwilson@dmp.com	
DESIGN:	Models XR150, XR350, and XR550 combination fire and burglary alarm control units. Local, remote station, proprietary and central station services. Models may have a combination of the following suffixes: D (dialer), N (network), E (encryption) or FC (fire control). Refer to listee's data sheet for additional detailed product description and operational considerations. System components:	
	XR150, XR350, XR550: Main Board	
	341, 349, 350, 350A, 352P 352X: Enclosures	
	352S: Battery Enclosure	
	630F: Supervised LCD Keypad	
	7070, 7070A, 7073, 7073A, 7170, 7170A, 7173, 7173A, 7570, 7570A, 7573, 7573A: LCD Keypads	
	325: Transformer Bracket	
	322, 323, 324, 324P, 327: Transformers	
	711, 714, 714-8, 714-16, 715, 715-8, 715-16: Zone Expanders	
	711S: Zone Expander (NOT for use with XR350)	
	716: Output Expander	
	717: Annunciator Module	
	860: Relay Module	
	893A: Dual Phone Line Module	
	734, 734N: Wiegand Interface	
	710: Bus Splitter	
	270: Network Transient Suppression Module	
	277: Trouble Sounder	
	9060, 9063: Wireless Keypads	
	263C, 263H: Cellular Communicator (May be used as the standalone primary	



CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

	communicator)		
	263LTE, 263LTE-FN: Cellular Communicator (NOT for use with XR350) (May be use the standalone primary communicator)		
	865, 866, 867: Indicating Module		
	869: Initiating Module		
	303: Reset/Silence Switch		
	1100X, 1100XH: RF Wireless Receiver		
	1100R: Wireless Repeater		
	1103: Wireless Transmitter		
	1135: Wireless Siren		
	*271: Ground Fault Detector Module		
RATING:	120 VAC, 0.5 A, 60 Hz		
INSTALLATION:	In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.		
MARKING:	Listee's name, model number, rating, and UL label.		
APPROVAL:	Listed as combination fire and burglary alarm control units for use with separately listed electrically compatible initiating and indicating devices. Refer to listee's Installation Instructions Manual for details.		
NOTES:	The Fire Alarm Verification Feature (delay of fire alarm signal), the maximum Retard/Reset/Restart period shall not exceed 30 seconds.		
	Burglary and other non-fire functions were not examined.		

5-20-24 MH

*Revised





CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION OFFICE OF THE STATE FIRE MARSHAL FIRE ENGINEERING & INVESTIGATIONS DIVISION **BUILDING MATERIALS LISTING PROGRAM**

LISTING SERVICE

This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an

endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.		
Pate Issued: 06/10/2024	Listing Expires: 06/30/2025	
authorized By: David Castillo , Program Coordinator Fire Engineering & Investigations Division		