Dealer Admin™



FEATURE UPDATE | DECEMBER 2021

New Features

Effective December 9th, 2021, Dealer Admin is updated to Version 2.73.0.

Central Station Integration

Dealer Admin now integrates with central station automation so connection status can be monitored and the system can be put on test remotely. These compatible central stations include:

- Rapid Response
- AlarmWatch
- Affiliated Monitoring
- CMS
- Other (for dealers who own and operate their own central station)

Add an Integration

Requirement: To manage integrations, you must have either an Administrator role or a custom role that allows you to view, add, edit, and delete Central Stations (previously called Receivers).

To add an integration, complete the following steps.

- 1. Go to Settings > Central Station.
- 2. In **Central Station**, select 🕂 Add.
- 3. Select a central station. To add a custom integration, select **Other** and follow the onscreen directions.
- 4. Enter the automation username and password.
- 5. To allow users in Virtual Keypad to create an emergency contacts list, select **Emergency Contacts**.
- 6. To allow users to place the system on test remotely from Virtual Keypad or Dealer Admin and Tech APP, select **Place System on Test**.
- 7. Select Save.

🔯 Dealer Admin					2	yourname@gmail.com Administrator
Central Station Settin	ngs					dy de la companya de la compa
Central Stations +						\wp Search \lor
AlarmWatch CONNECTED			» 💼			A Customers 1
Receivers						Dealer Dashboard
						J ^{Ce} Tools ~
Receiver Number	Automation Prefix	IP	Port	Description		Personnel ~
1	101	192.168.0.0	2001			News Items
2	102	192.168.0.0	2001			A Dealer Resources
3	103	192.168.0.0	2001		۵۰ 🛱	
						S Customer Referrals
						🔓 Billing
						د المعالم المعالم المحالي محالي المحالي محالي مح
						Central Station
						Dealer Programming Templates

View Central Station Communication Status

You can view the central station connection status for a single system in **System Status**. You can also view the status for all of a customer's systems at once by opening the **Customer Summary**.

Place the System on Test

- 1. To put the system on test, open the system and go to **System Status**.
- 2. Select Place System on Test, then select a duration.

WARNING: For the number of hours that you specify, the system will send signals to the central station but emergency services will not be contacted.

3. To start the test, select **Confirm**.

HomeMart - System Status I Arming I Arming I Audian Perimeter The system contraction Perimeter I Audian Perimeter I Audian Perimeter I Audian I Audian Perimeter I Audian I Audiana	🥺 Dealer Admin			yourname@gmail.com Administrator
C Arming C bours 3 hours 4 hours C ourse 4 hours <t< th=""><th>HomeMart - System Status CONNECTED</th><th>Place System On Test During a system test, the alarm system will continue to send messages to the monitoring center, but emergency services will not be contacted.</th><th>Put System On Test</th><th></th></t<>	HomeMart - System Status CONNECTED	Place System On Test During a system test, the alarm system will continue to send messages to the monitoring center, but emergency services will not be contacted.	Put System On Test	
All Perimeter Your system is currently diarmed. Winneklart Other Parameter All Comain Fast Programming Print Progr	O Arming	2 hours 3 hours 4 hours	O Refresh	Search 🗸
Nour system is currently disarmed. Image: Comparison of the currently disarmed. Image: Comparison of the currently disarmed. Nour system is currently disarmed. Fault Programming Fault Programming Full Programming Programming Programming Programming Remote Update Schodules Schodules System Reinformation System Reports System Reports System Status System Status	All Perim			Dealer Dashboard
Fast Programming Full Programming Print Programming Remote Update Schedules System Nahylics System Reports System Reports System Status	Your system is currently disarmed.			U HomeMart
System Status				Fast Programming Full Programming Print Programming Remote Update Schedules System Analytics System Information System Reports
System Tests User Codes				System Status System Tests User Codes

Configure Receivers

In the new Central Station page, set up your Receivers using prefixes as needed to ensure each panel is linked properly to automation.

- 1. In the menu, go to **Settings** > **Central Stations**.
- 2. Select 🕂 Add.
- 3. Enter the receiver's **Receiver Number**, **Automation Prefix**, **IP Address**, **Port**, and **Central Station**. If desired, enter a brief description about the receiver in **Description**.
- 4. Select Save.

User Interface Improvements

- In Settings, we changed the name of the Receivers page to Central Station
- In Personnel > Custom Roles, we changed the name of the Receivers custom role to Central Stations

More Information

To learn more, refer to the following documentation:

Dealer Admin Help: <u>Central Station</u>